



# Nokian TR Forest 12.4-24 12PR – T482192

TT = TUBE-TYPE, to be fitted with tube

Product code	Size	LI/SS	PR	Pattern TR	TT/TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Inflation pressure		Forestry Load capacity kg/lbs		Load capacity kg/lbs										Total tread depth		Tread depth measured on top of tie-bar	
								mm	in	mm	in	mm	in	mm	in	mm	in	kPa	psi	10 km/h	5 mph	10 km/h	5 mph	20 km/h	10 mph	30 km/h	20 mph	40 km/h	25 mph	50 km/h	30 mph	mm	32 nds in
T482192	12.4-24	128 A8 / 125 B	12	FS FOREST	TT	DW11	DW10, W11, W10, W9	315	12.4	1 160	45.7	538	21.2	3 443	135.6	350	51	2 215	4 885	2 700	5 950	2 215	4 885	1 930	4 255	1 800	3 970	1 640	3 615	41	52	-	-

## LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation Pressure		Road 50 km/h / 30 mph		Road 40 km/h / 25 mph		Road 30 km/h / 20 mph		Road 20 km/h / 12.5 mph		Road 10 km/h / 5 mph		Forestry service (LT) 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
120	17	930	2 050	1 020	2 250	1 090	2 405	1 255	2 765	1 530	3 375	1 255	2 765
160	23	1 130	2 490	1 240	2 735	1 325	2 920	1 525	3 360	1 860	4 100	1 525	3 360
200	29	1 245	2 745	1 370	3 020	1 465	3 230	1 685	3 715	2 055	4 530	1 685	3 715
240	35	1 320	2 910	1 450	3 195	1 550	3 415	1 785	3 935	2 175	4 795	1 785	3 935
280	41	1 450	3 195	1 595	3 515	1 705	3 760	1 960	4 320	2 395	5 280	1 960	4 320
320	46	1 565	3 450	1 720	3 790	1 840	4 055	2 115	4 665	2 580	5 690	2 115	4 665
350	51	1 640	3 615	1 800	3 970	1 930	4 255	2 215	4 885	2 700	5 950	2 215	4 885

## LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
		Water		Salt (CaCl <sub>2</sub> )		Total weight increase			
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
150	40	115	30	92	24	47	105	139	305

## TUBES AND VALVES

USE ALWAYS WITH TUBE

Tube product code	Valve tube-type
T55100	TR 218 A