



Nokian TR Forest 13.6-24 10PR – T482198

TT = TUBE-TYPE, to be fitted with tube

Product code	Size	LI/SS	PR	Pattern TR	TT/ TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Inflation pressure		Forestry Load capacity kg/lbs		Load capacity kg/lbs										Total tread depth		Tread depth measured on top of tie-bar	
								mm	in	mm	in	mm	in	mm	in	kPa	psi	10 km/h	5 mph	10 km/h	5 mph	20 km/h	10 mph	30 km/h	20 mph	40 km/h	25 mph	50 km/h	30 mph	mm	32 nds in	mm	32 nds in
T482198	13.6-24	128 A8 / 125 B	10	FS FOREST	TT	DW12	DW12, DW11, W12, W11	345	13.6	1 210	47.6	548	21.6	3 512	138.3	250	36	2 215	4 885	2 700	5 950	2 215	4 885	1 930	4 255	1 800	3 970	1 640	3 615	46	58	-	-

LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation Pressure		Road 50 km/h / 30 mph		Road 40 km/h / 25 mph		Road 30 km/h / 20 mph		Road 20 km/h / 12.5 mph		Road 10 km/h / 5 mph		Forestry service (LT) 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
120	17	1 125	2 480	1 235	2 725	1 320	2 910	1 520	3 350	1 855	4 090	1 520	3 350
160	23	1 375	3 030	1 510	3 330	1 615	3 560	1 855	4 090	2 265	4 995	1 855	4 090
200	29	1 505	3 320	1 655	3 650	1 770	3 900	2 035	4 485	2 485	5 480	2 035	4 485
250	36	1 640	3 615	1 800	3 970	1 930	4 255	2 215	4 885	2 700	5 950	2 215	4 885

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
				Water		Salt (CaCl ₂)		Total weight increase	
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
180	50	135	35	111	29	56	125	167	370

TUBES AND VALVES

USE ALWAYS WITH TUBE

Tube product code	Valve tube-type
T55105	TR 218 A