



Nokian TR Forest 16.9-28 14PR – T483301

TT = TUBE-TYPE, to be fitted with tube

Product code	Size	LI/SS	PR	Pattern TR	TT/TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Inflation pressure		Forestry Load capacity kg/lbs		Load capacity kg/lbs										Total tread depth		Tread depth measured on top of tie-bar	
								mm	in	mm	in	mm	in	mm	in	kPa	psi	10 km/h	5 mph	10 km/h	5 mph	20 km/h	10 mph	30 km/h	20 mph	40 km/h	25 mph	50 km/h	30 mph	mm	32 nds in	mm	32 nds in
T483301	16.9-28	145 A8 / 142 B	14	FOREST	TT	DW15	DW14, W15L, W14L	429	16.9	1 435	56.5	662	26.1	4 280	168.5	270	39	3 565	7 860	4 350	9 590	3 565	7 860	3 120	6 880	2 900	6 395	2 640	5 820	42	53	37	47

LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation Pressure		Road 50 km/h / 30 mph		Road 40 km/h / 25 mph		Road 30 km/h / 20 mph		Road 20 km/h / 12.5 mph		Road 10 km/h / 5 mph		Forestry service (LT) 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
120	17	1 730	3 815	1 900	4 190	2 035	4 485	2 335	5 150	2 850	6 285	2 335	5 150
160	23	2 110	4 650	2 320	5 115	2 480	5 465	2 855	6 295	3 480	7 670	2 855	6 295
200	29	2 320	5 115	2 550	5 620	2 730	6 020	3 135	6 910	3 825	8 435	3 135	6 910
240	35	2 460	5 425	2 705	5 965	2 895	6 380	3 325	7 330	4 060	8 950	3 325	7 330
270	39	2 640	5 820	2 900	6 395	3 120	6 880	3 565	7 860	4 350	9 590	3 565	7 860

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
				Water		Salt (CaCl ₂)		Total weight increase	
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
335	90	250	65	206	54	105	230	311	685

TUBES AND VALVES

USE ALWAYS WITH TUBE

Tube product code	Valve tube-type
T55370	TR 218 A