



# Nokian TR Forest 16.9-30 14PR – T483810

TT = TUBE-TYPE, to be fitted with tube

Product code	Size	LI/SS	PR	Pattern TR	TT/TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Inflation pressure		Forestry Load capacity kg/lbs		Load capacity kg/lbs										Total tread depth		Tread depth measured on top of tie-bar	
								mm	in	mm	in	mm	in	mm	in	mm	in	kPa	psi	10 km/h	5 mph	10 km/h	5 mph	20 km/h	10 mph	30 km/h	20 mph	40 km/h	25 mph	50 km/h	30 mph	mm	32 nds in
T483810	16.9-30	144 A8 / 141 B	14	FS FOREST	TT	DW15	DW14, W15L, W14L	429	16.9	1 485	58.5	683	26.9	4 361	171.7	260	38	3 445	7 595	4 200	9 260	3 445	7 595	3 000	6 615	2 800	6 175	2 550	5 620	45	57	-	-

## LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation Pressure		Road 50 km/h / 30 mph		Road 40 km/h / 25 mph		Road 30 km/h / 20 mph		Road 20 km/h / 12.5 mph		Road 10 km/h / 5 mph		Forestry service (LT) 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
160	23	2 110	4 650	2 320	5 115	2 480	5 465	2 855	6 295	3 480	7 670	2 855	6 295
200	29	2 395	5 280	2 630	5 800	2 815	6 205	3 235	7 130	3 945	8 695	3 235	7 130
240	35	2 550	5 620	2 800	6 175	3 000	6 615	3 445	7 595	4 200	9 260	3 445	7 595

## LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
				Water		Salt (CaCl <sub>2</sub> )		Total weight increase	
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
360	95	270	70	222	59	113	250	334	735

## TUBES AND VALVES

USE ALWAYS WITH TUBE

Tube product code	Valve tube-type
T55371	TR 218 A