



Nokian TR Forest 16.9-34 14PR – T484390

TT = TUBE-TYPE, to be fitted with tube

Product code	Size	LI/SS	PR	Pattern TR	TT/TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Inflation pressure		Forestry Load capacity kg/lbs		Load capacity kg/lbs										Total tread depth		Tread depth measured on top of tie-bar	
								mm	in	mm	in	mm	in	mm	in	kPa	psi	10 km/h	5 mph	10 km/h	5 mph	20 km/h	10 mph	30 km/h	20 mph	40 km/h	25 mph	50 km/h	30 mph	mm	32 nds in	mm	32 nds in
T484390	16.9-34	146 A8 / 143 B	14	FS FOREST	TT	DW15	DW14, W15L, W14L	429	16.9	1 585	62.4	742	29.2	4 599	181.1	260	38	3 690	8 135	4 500	9 920	3 690	8 135	3 220	7 100	3 000	6 615	2 730	6 020	45	57	-	-

LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation Pressure		Road 50 km/h / 30 mph		Road 40 km/h / 25 mph		Road 30 km/h / 20 mph		Road 20 km/h / 12.5 mph		Road 10 km/h / 5 mph		Forestry service (LT) 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
160	23	2 350	5 180	2 580	5 690	2 760	6 085	3 175	7 000	3 870	8 530	3 175	7 000
200	29	2 565	5 655	2 820	6 215	3 015	6 645	3 470	7 650	4 230	9 325	3 470	7 650
240	35	2 730	6 020	3 000	6 615	3 220	7 100	3 690	8 135	4 500	9 920	3 690	8 135

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
				Water		Salt (CaCl ₂)		Total weight increase	
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
390	105	295	80	240	63	122	270	362	800

TUBES AND VALVES

USE ALWAYS WITH TUBE

Tube product code	Valve tube-type
T55391	TR 218 A