



Nokian TR Forest 18.4-34 14PR – T484420

TT = TUBE-TYPE, to be fitted with tube

Product code	Size	LI/SS	PR	Pattern TR	TT/TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Inflation pressure		Forestry Load capacity kg/lbs		Load capacity kg/lbs										Total tread depth		Tread depth measured on top of tie-bar	
								mm	in	mm	in	mm	in	mm	in	kPa	psi	10 km/h	5 mph	20 km/h	10 mph	30 km/h	20 mph	40 km/h	25 mph	50 km/h	30 mph	mm	32 nds in	mm	32 nds in		
T484420	18.4-34	154 A8 / 151 B	14	FS FOREST	TT	DW16	DW15, W16L, W15L	467	18.4	1 650	65.0	765	30.1	4 825	190.0	260	38	4 615	10 175	5 625	12 400	4 615	10 175	4 020	8 860	3 750	8 265	3 420	7 540	48	61	43	54

LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation Pressure		Road 50 km/h / 30 mph		Road 40 km/h / 25 mph		Road 30 km/h / 20 mph		Road 20 km/h / 12.5 mph		Road 10 km/h / 5 mph		Forestry service (LT) 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
120	17	2 340	5 160	2 570	5 665	2 750	6 065	3 160	6 965	3 855	8 500	3 160	6 965
160	23	2 865	6 315	3 150	6 945	3 370	7 430	3 875	8 545	4 725	10 415	3 875	8 545
200	29	3 140	6 920	3 450	7 605	3 690	8 135	4 245	9 360	5 175	11 410	4 245	9 360
250	36	3 420	7 540	3 750	8 265	4 020	8 860	4 615	10 175	5 625	12 400	4 615	10 175

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
		Water		Salt (CaCl ₂)		Total weight increase			
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
480	125	360	95	295	78	151	335	446	985

TUBES AND VALVES

USE ALWAYS WITH TUBE

Tube product code	Valve tube-type
T55391	TR 218 A