



Nokian TR Multiplus 500/65R24 – T445410

TL = TUBELESS, may be fitted with or without tube

Product code	Size	LI/SS	Pattern TR	TT/TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Inflation pressure		Load capacity kg/lbs						Tread depth	
							mm	in	mm	in	mm	in	mm	in	kPa	psi	30 km/h	20 mph	40 km/h	25 mph	50 km/h	30 mph	mm	32 nds in
T445410	500/65R24	142 A8/139 B	Multiplus	TL	W15L	W16L, W14L, W13	480	18.9	1 244	49.0	575	22.6	3 735	147.0	240	35	2 840	6 260	2 650	5 840	2 430	5 355	48	61

LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation pressure ¹⁾		Road Service 50 km/h / 30 mph		Road Service 40 km/h / 25 mph		Road Service 30 km/h / 20 mph		Pull Service in Forest 10 km/h / 5 mph		Field Service ²⁾ 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
240	35	2 430	5 355	2 650	5 840	2 840	6 260	3 180	7 010	3 980	8 775
160	23	1 850	4 080	2 060	4 540	2 200	4 850	-	-	3 090	6 810
80	12	1 285	2 835	1 400	3 085	1 500	3 305	-	-	2 100	4 630

1) The maximum tire inflation pressure in forestry use is 320 kPa / 46 psi without increase in the load values.

2) For field applications with high and sustained torque, values for road service 30 km/h / 20 mph are applied.

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
				Water		Salt (CaCl ₂)		Total weight increase	
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
270	70	205	55	166	44	85	185	251	555

TUBES AND VALVES

Valve tubeless	Tube product code	Valve tube-type
TR 618 A	T55116	TR 218 A