



Nokian TR Multiplus 600/65R38 – T445414

TL = TUBELESS, may be fitted with or without tube

Product code	Size	LI/SS	Pattern TR	TT/TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Inflation pressure		Load capacity kg/lbs						Tread depth	
							mm	in	mm	in	mm	in	mm	in	kPa	psi	30 km/h	20 mph	40 km/h	25 mph	50 km/h	30 mph	mm	32 nds in
T445414	600/65R38	159 A8/156 B	Multiplus	TL	DW18L	W16L,W18L, DW20B	575	22.6	1 753	69.0	809	31.9	5 290	208.3	240	35	4 680	10 320	4 375	9 645	4 000	8 820	52	66

LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation pressure ¹⁾		Road Service 50 km/h / 30 mph		Road Service 40 km/h / 25 mph		Road Service 30 km/h / 20 mph		Pull Service in Forest 10 km/h / 5 mph		Field Service ²⁾ 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
240	35	4 000	8 820	4 375	9 645	4 680	10 320	5 250	11 575	6 560	14 460
160	23	3 150	6 945	3 450	7 605	3 690	8 135	-	-	5 180	11 420
80	12	2 120	4 675	2 300	5 070	2 460	5 425	-	-	3 450	7 605

- 1) The maximum tire inflation pressure in forestry use is 320 kPa / 46 psi without increase in the load values.
 2) For field applications with high and sustained torque, values for road service 30 km/h / 20 mph are applied.

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
				Water		Salt (CaCl ₂)		Total weight increase	
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
640	170	480	125	394	104	201	445	595	1 310

TUBES AND VALVES

Valve tubeless	Tube product code	Valve tube-type
TR 618 A	T55445	TR218A