



Nokian TR Multiplus 650/65R38 – T445415

TL = TUBELESS, may be fitted with or without tube

Product code	Size	LI/SS	Pattern TR	TT/TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Inflation pressure		Load capacity kg/lbs						Tread depth	
							mm	in	mm	in	mm	in	mm	in	mm	in	kPa	psi	30 km/h	20 mph	40 km/h	25 mph	50 km/h	30 mph
T445415	650/65R38	164 A8/160 B	Multiplus	TL	DW20B	DW18	645	25.4	1 811	71.3	838	33.0	5 485	215.9	240	35	5 350	11 795	5 000	11 025	4 500	9 920	53	67

LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation pressure ¹⁾		Road Service 50 km/h / 30 mph		Road Service 40 km/h / 25 mph		Road Service 30 km/h / 20 mph		Pull Service in Forest 10 km/h / 5 mph		Field Service ²⁾ 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
240	35	4 500	9 920	5 000	11 025	5 350	11 795	6 000	13 230	7 500	16 535
160	23	3 550	7 825	3 875	8 545	4 150	9 150	-	-	5 810	12 810
80	12	2 360	5 205	2 575	5 675	2 760	6 085	-	-	3 860	8 510

- 1) The maximum tire inflation pressure in forestry use is 320 kPa / 46 psi without increase in the load values.
 2) For field applications with high and sustained torque, values for road service 30 km/h / 20 mph are applied.

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
		Water		Salt (CaCl ₂)		Total weight increase			
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
775	205	580	155	477	126	243	535	720	1 585

TUBES AND VALVES

Valve tubeless	Tube product code	Valve tube-type
TR 618 A	-	-