



Nokian TRI 2 460/65R24 – T445393

| Product code | Size | LI/SS | Rim TW profile may replace DW | Permitted rims | Width | | Diameter | | Loaded static radius | | Rolling circumference | | Speed Radius Index SRI | Maximum inflation pressure | | Load capacity kg / lbs | | | | | | | | Total tread depth | | Tread depth measured on top of tie-bar | |
|--------------|-----------|-------|--------------------------------------|--------------------------|-------|------|----------|------|----------------------|------|-----------------------|-------|------------------------|----------------------------|----|------------------------|--------|---------|--------|---------|--------|---------|--------|-------------------|-----------|--|-----------|
| | | | | | mm | in | mm | in | mm | in | mm | in | | mm | in | 30 km/h | 20 mph | 40 km/h | 25 mph | 50 km/h | 30 mph | 65 km/h | 40 mph | mm | 32 nds in | mm | 32 nds in |
| T445393 | 460/65R24 | 151 D | DW14L | W15L, W16L, DW15L, DW16L | 454 | 17.9 | 1 208 | 47.6 | 550 | 21.7 | 3 638 | 143.2 | 575 | 400 | 58 | 4 160 | 9 170 | 4 000 | 8 820 | 3 760 | 8 290 | 3 450 | 7 605 | 28 | 35 | 23.5 | 30 |

LOAD CAPACITY VALUES AT DIFFERENT SPEEDS AND PRESSURES

| Constant | | 0.8 bar | 12 psi | 1.2 bar | 17 psi | 1.6 bar | 23 psi | 2.0 bar | 29 psi | 2.4 bar | 35 psi | 3.2 bar | 46 psi | 4.0 bar | 58 psi |
|----------|------|---------|--------|---------|--------|---------|--------|---------|--------|---------|--------|---------|--------|---------|--------|
| km/h | mph | kg | lbs | kg | lbs | kg | lbs | kg | lbs | kg | lbs | kg | lbs | kg | lbs |
| 0 | 0 | 2 800 | 6 175 | 3 580 | 7 890 | 4 380 | 9 655 | 5 160 | 11 375 | 5 940 | 13 095 | 7 500 | 16 535 | 9 200 | 20 280 |
| 5 | 2.5 | 1 770 | 3 900 | 2 250 | 4 960 | 2 760 | 6 085 | 3 260 | 7 185 | 3 740 | 8 245 | 4 720 | 10 405 | 5 800 | 12 785 |
| 10 | 5 | 1 520 | 3 350 | 1 940 | 4 275 | 2 380 | 5 245 | 2 800 | 6 175 | 3 220 | 7 100 | 4 080 | 8 995 | 5 000 | 11 025 |
| 15 | 10 | 1 380 | 3 040 | 1 760 | 3 880 | 2 150 | 4 740 | 2 540 | 5 600 | 2 910 | 6 415 | 3 680 | 8 115 | 4 520 | 9 965 |
| 20 | 12.5 | 1 330 | 2 930 | 1 690 | 3 725 | 2 080 | 4 585 | 2 450 | 5 400 | 2 810 | 6 195 | 3 560 | 7 850 | 4 360 | 9 610 |
| 25 | 15 | 1 290 | 2 845 | 1 650 | 3 640 | 2 020 | 4 455 | 2 380 | 5 245 | 2 730 | 6 020 | 3 460 | 7 630 | 4 240 | 9 350 |
| 30 | 20 | 1 270 | 2 800 | 1 620 | 3 570 | 1 980 | 4 365 | 2 330 | 5 135 | 2 680 | 5 910 | 3 380 | 7 450 | 4 160 | 9 170 |
| 35 | 22.5 | 1 240 | 2 735 | 1 590 | 3 505 | 1 940 | 4 275 | 2 290 | 5 050 | 2 630 | 5 800 | 3 320 | 7 320 | 4 080 | 8 995 |
| 40 | 25 | 1 215 | 2 680 | 1 550 | 3 415 | 1 900 | 4 190 | 2 240 | 4 940 | 2 575 | 5 675 | 3 250 | 7 165 | 4 000 | 8 820 |
| 45 | 28 | - | - | 1 510 | 3 330 | 1 850 | 4 080 | 2 180 | 4 805 | 2 500 | 5 510 | 3 160 | 6 965 | 3 880 | 8 555 |
| 50 | 30 | - | - | 1 460 | 3 220 | 1 790 | 3 945 | 2 110 | 4 650 | 2 430 | 5 355 | 3 060 | 6 745 | 3 760 | 8 290 |
| 65 | 40 | - | - | 1 360 | 3 000 | 1 650 | 3 640 | 1 950 | 4 300 | 2 240 | 4 940 | 2 800 | 6 175 | 3 450 | 7 605 |

LIQUID AND SALT BALLASTING

| Tire volume 100% | | Water filling (75%) | | Water / salt filling (75% / -30°C / -22°F) | | | | | |
|------------------|----------|---------------------|----------|--|----------|---------------------------|-----|-----------------------|-----|
| | | | | Water | | Salt (CaCl ₂) | | Total weight increase | |
| l | gal (US) | l | gal (US) | l | gal (US) | kg | lbs | kg | lbs |
| 270 | 71 | 205 | 54 | 166 | 44 | 85 | 185 | 251 | 555 |

TUBES AND VALVES

| Valve tubeless | Tube product code | Valve tube-type |
|----------------|-------------------|-----------------|
| TR 618 A | T55111 | TR 218A |