

# 540/65R30 155D/152E NOKIAN TYRES GROUND KING SB TL

A crossover tire for mixed agricultural work

|                   |                |
|-------------------|----------------|
| PRODUCT CODE      | T445728        |
| APPLICATION       | Tractor        |
| LI / SPEED SYMBOL | 155D (152E)    |
| RIM RECOMMENDED   | DW18L          |
| RIM PERMITTED     | DW16L          |
| TYPE APPROVAL     | E8 106R-001798 |



## LOAD CAPACITY FOR TRACTOR, KG

### Tractor

| Pressure (kPa) | Speed (km/h) |      |      |      |      |      |      |      |      |      |      |      |      |      |
|----------------|--------------|------|------|------|------|------|------|------|------|------|------|------|------|------|
|                | 5            | 10   | 15   | 20   | 25   | 30   | 35   | 40   | 45   | 50   | 55   | 60   | 65   | 70   |
| 80             | 3060         | 2700 | 2410 | 2215 | 2135 | 2070 | 2015 | 1970 | 1925 | 1890 | 1855 | 1825 | 1800 | 1640 |
| 120            | 3910         | 3450 | 3080 | 2830 | 2725 | 2645 | 2575 | 2520 | 2460 | 2415 | 2370 | 2335 | 2300 | 2095 |
| 160            | 4635         | 4090 | 3650 | 3350 | 3230 | 3135 | 3050 | 2985 | 2915 | 2860 | 2805 | 2765 | 2725 | 2480 |
| 200            | 5230         | 4615 | 4120 | 3780 | 3645 | 3535 | 3445 | 3365 | 3290 | 3230 | 3165 | 3120 | 3075 | 2800 |
| 240            | 5695         | 5025 | 4490 | 4120 | 3970 | 3855 | 3750 | 3670 | 3585 | 3520 | 3450 | 3400 | 3350 | 3050 |
| 280            | 6205         | 5475 | 4890 | 4490 | 4325 | 4200 | 4090 | 3995 | 3905 | 3835 | 3760 | 3705 | 3650 | 3320 |
| 320            | 6590         | 5815 | 5195 | 4765 | 4590 | 4455 | 4340 | 4245 | 4145 | 4070 | 3990 | 3935 | 3875 | 3525 |

## TIRE DIMENSIONS

|                         | New tire | Max. in service |
|-------------------------|----------|-----------------|
| OVERALL DIAMETER        | 1475 mm  | 1492 mm         |
| TIRE WIDTH              | 535 mm   | 567 mm          |
| PATTERN DEPTH           | 50 mm    |                 |
| MAX. INFLATION PRESSURE | 320 kPa  |                 |

|                               |  |
|-------------------------------|--|
| STATIC LOADED RADIUS          | 679 mm @ 3875 kg / 320 kPa   |
| DYNAMIC ROLLING CIRCUMFERENCE | 4451 mm @ 3875 kg / 320 kPa  |
| DYNAMIC ROLLING RADIUS        | 708 mm @ 3875 kg / 320 kPa   |
| SPEED RADIUS INDEX            | 700  |
| TUBELESS VALVE                | TR618A   |
| BELT MATERIAL                 | Steel  |
| MARKINGS                      | M+S  |
| STUDDABLE                     | Yes<br>Marked stud positions on tread<br>Number of studs 144 pcs<br>Recommended stud 12-20,12-23-12-24,16-19 |
| VOLUME                        | 435 l 100%<br>326 l 75%  |

**WATER AND SALT BALLASTING**

(CaCl<sub>2</sub>, 75%, -30°C) Always use a tube when filled with water/salt.

| Tire volume 100% |         | Water filling 75% |         | Water/salt filling (75% / -30°C) |         |      |     | Total weight increase |     |
|------------------|---------|-------------------|---------|----------------------------------|---------|------|-----|-----------------------|-----|
|                  |         |                   |         | Water                            |         | Salt |     |                       |     |
| Litres           | Gallons | Litres            | Gallons | Litres                           | Gallons | kg   | lbs | kg                    | lbs |
| 435              | 115     | 326               | 86      | 268                              | 71      | 136  | 301 | 404                   | 891 |

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)