

HL10

Powerfull nylon cord body, strong heel construction provide high performance and durability against impacts.



FORKLIFT HL 10

TIRE SIZE	PR	TT/TL	LOAD INDEX	SPEED SYMBOL	INFLATING PRESSURE (psi)	RIM		INFLATED DIMENSIONS (NO LOAD)		LOAD CAPACITY PER TIRE (KG)
						RECOM. (INCHES)	PERMITTED (INCHES)	SECTION WIDTH MIN-MAX	RADIUS (MM)	
23x5-13	10	TT	121	A5	116	3,75P	-	155	635	1150
4.00-8	8	TT	94	A5	131	31/4I	3.00D	115	414	670
5.00-8	8	TT	106	A5	120	31/4I	-	132	132	950
5.00-8	10	TT	111	A5	145	3.00D	3 1/4 I	132	467	1090
18x7-8	16	TT	125	A5	145	4.33R	-	173	462	1650
6.00-9	12	TT	121	A5	145	4.00E	-	160	540	1450
21x8-9	14	TT	131	A5	131	6.00E	-	200	535	1950
6.50-10	12	TT	125	A5	131	5.00F	5.50F	177	588	1650
23x9-10	20	TT	142	A5	145	6.50F	-	225	595	2650
7.00-12	14	TT	134	A5	131	5.00S	-	192	672	2120
27x10-12	14	TT	143	A5	102	8.00G	-	255	690	2725
8.15-15	14	TT	146	A5	145	7.0	-	216	707	3000
8.25-15	16	TT	152	A5	134	6.5	7	234	836	3550

