

NT 30

Trailer

PERFORMANCE INFORMATION

Special trailer tire



FEATURES

Long life / Durability

- Durable nylon carcass structure
- Special tread compound for heavy load conditions
- High resistance against cuts and tread wear with special tread geometry design.

Heavy load capacity / Self Cleaning

- Special tread structure
- Strong carcass structure, high load capacity and self-cleaning property

SIZES 9.00-16



Trailer • Characteristics of **NT 30**

	Tire Size	PR	TT/TL	Load/Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg				
					Recom (inch)	Permitted (inch)	Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h				
												10	30	40	50	
	9.00-16	12	TT	125/A6	6.00F	5.50F, 6LB	247	881	2650	388	47 / 3.2	1645	1450	1320	1160	
											52 / 3.6	1810	1595	1450	1275	
											58 / 4.0	2060	1815	1650	1450	
		14	TT	128/A6							52 / 3.6	1895	1680	1530	1345	
											58 / 4.0	2075	1840	1670	1470	
											67 / 4.6	2235	1980	1800	1585	
		16	TT	131/A6							67 / 4.6	2235	1790	1600	1405	
											72 / 5.0	2455	1965	1755	1545	
											80 / 5.5	2731	2185	1950	1715	

• Load capacity on recommended speed and pressure is stated with dark colour.



DESCRIPTION

- * For load capacity on various speed ratings, and inflation figures, please consult your sales representative.
- ** Load capacity on standard speed and weight

- Our company is entitled to make any change on any information in this catalogue, without further notice.
- This catalogue annuls all the previous catalogues
- All figures are for reference; our company is not responsible for printing errors.