

TA 330

Tractor
Rear

PERFORMANCE INFORMATION

R1 farm rear tire with high resistance/traction and deep tread design for tough operating conditions



FEATURES

Long service life / Durability

- Strong nylon carcass structure provides optimum durability
- Tread compound specially developed for stony/tough terrains provides high resistance against wear and cuts
- Tread profile with extra wide tread base provides perfect resistance to tread base fatigue

Ease of use

- Wide and reinforced body provides easy grip, high traction and reduced slipping
- Special tread design for tough terrains provides superior performance

SIZES 30.5L-32

Tractor Rear • Characteristics of TA 330

Tire Size	PR	TT/TL	Load/Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg					
				Recom (inch)	Permitted (inch)	Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h					
											10	15	20	25	30	40
30.5L32	12	TL	158 / A8	DW27B	DHB27, DH27B, DH27H	770	1840	5485	828	20 / 1.4	-	-	-	-	4750	4250

- Load capacity on recommended speed and pressure is stated with dark colour.
- 30.5 L32 18PR is also available for trailers.

DESCRIPTION

- * For load capacity on various speed ratings, and inflation figures, please consult your sales representative.
- ** Load capacity on standard speed and weight

- Our company is entitled to make any change on any information in this catalogue, without further notice.
- This catalogue annuls all the previous catalogues
- All figures are for reference; our company is not responsible for printing errors.