

TD 18

Tractor
Front

PERFORMANCE INFORMATION

Ideal tractor front tire for field and short distance road usage



FEATURES

Long service life / Durability

- Strong nylon carcass structure provides optimum durability
- Improved tread compound provides high resistance against wear and cuts
- Strong center and shoulder design provides high resistance to side impacts and tread base fatigue

Ease of use

- Special tread geometry provides easy steering
- Flexible carcass structure prevents sinking

SIZES 6.50-16 • 7.50-18 • 7.50-20

Tractor Front - Characteristics of TD 18

Tire Size	PR	TT/TL	Load/Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg					
				Recom (inch)	Permitted (inch)	Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h					
											10	15	20	25	30	40
6.50-16	6	TT	91 / A6	4.50E	4.00E, 5K, 5.50F, 5.50F	175	760	2280	350	38 / 2.6	840	800	755	645	560	450
										41 / 2.8	890	845	800	680	590	475
										45 / 3.1	925	880	830	705	615	495
	52 / 3.6	1015	965							910	775	675	540			
	57 / 3.9	1050	1000							945	805	700	560			
	61 / 4.2	1095	1045							985	840	730	585			
7.50-18	8	TT	106 / A6	5.50F	-	205	860	2580	396	45 / 3.1	1325	1265	1195	1020	885	710
										49 / 3.4	1390	1325	1250	1065	925	740
										54 / 3.7	1425	1360	1285	1095	950	760
7.50-20	8	TT	108 / A6	5.50F	5.00F	205	915	2727	420	42 / 2.9	1380	1315	1245	1060	920	735
										45 / 3.1	1440	1375	1295	1105	960	770
										49 / 3.4	1500	1430	1350	1150	1000	800

• Load capacity on recommended speed and pressure is stated with dark colour.

DESCRIPTION

* For load capacity on various speed ratings, and inflation figures, please consult your sales representative.

** Load capacity on standard speed and weight

- Our company is entitled to make any change on any information in this catalogue, without further notice.
- This catalogue annuls all the previous catalogues
- All figures are for reference; our company is not responsible for printing errors.