

FLOTATION IMPLEMENT TYRES

- Suitably designed for on and off-the-road use, in all weather conditions.
- Patterns are engineered to provide excellent traction to drive wheels & are suited for both implement & industrial / construction applications.



FLOTATION KING

SIZE	PATTERN	PLY RATING	RIM WIDTH	TT or TL	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY				INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	40KPH	50KPH	25 MPH	30 MPH	bar	psi		kmph	mph
															MAX LOAD	MAX LOAD	MAX LOAD	MAX LOAD					
400/60-15.5	FLOTATION KING	14	13.0	TL	400	15.7	875	34.4	381	15.0	2565	101.0	20	25	2731	2272	6010	5000	3.8	52	143	A8/40kmph	A8/25mph
	FLOTATION KING	18	13.0	TL	400	15.7	875	34.4	381	15.0	2565	101.0	20	25	3256	2772	7165	6100	4.5	65	149	A8/40kmph	A8/25mph
400/55-22.5	FLOTATION KING	16	13.0	TL	400	15.7	1020	40.1	432	17.0	3073	121.0	29	36	2574	2254	5510	4960	4.1	58	136	B/50 kmph	B/30mph
400/60-22.5	FLOTATION KING	16	11.75	TL	400	15.7	1070	42.1	483	19.0	3226	127.0	29	36	2806	2245	6175	4940	1.5	22	136	B/50 kmph	B/30mph
	FLOTATION KING	18	11.75	TL	400	15.7	1070	42.1	483	19.0	3226	127.0	29	36	3156	2504	6945	5510	3.8	55	140	B/50 kmph	B/30mph
385/65-22.5	FLOTATION KING	16	11.75	TL	385	15.2	1070	42.1	483	19.0	3226	127.0	29	36	2800	2245	6175	4940	3.6	22	136	B/50 kmph	B/30mph
	FLOTATION KING	18	11.75	TL	385	15.2	1070	42.1	483	19.0	3226	127.0	29	36	3150	2544	6945	5510	4.4	55	140	B/50 kmph	B/30mph
500/45-22.5	FLOTATION KING	16	16.0	TL	500	19.7	1050	42.1	457	18.0	3099	122.0	35	44	3080	2436	6780	5360	3.7	52	138	B/50 kmph	B/30mph
500/60-22.5	FLOTATION KING	16	16.0	TL	500	19.7	1170	46.1	508	20.0	3480	137.0	38	48	3456	3156	7605	6945	2.8	41	148	B/50 kmph	B/30mph
550/60-22.5	FLOTATION KING	16	16.0	TL	550	21.7	1240	48.8	533	21.0	3738	147.2	38	48	3760	3356	8270	7385	3.1	45	150	B/50 kmph	B/30mph
600/50-22.5	FLOTATION KING	16	20.0	TL	600	23.6	1170	46.1	508	20.0	3505	138.0	38	48	3600	3256	8050	7165	2.2	32	149	B/50 kmph	B/30mph
600/55-22.5	FLOTATION KING	16	20.0	TL	600	23.6	1230	48.4	533	21.0	3708	146.0	38	48	4010	3659	8820	8050	2.2	32	153	B/50 kmph	B/30mph

Tolerances: O.D. ± 2.5% - S.W. ± 2.5% - RC ± 2.5%