



AGRICULTURAL

IMPLEMENT TYRES

- Low section Implement tyres offering high load capacity with minimum soil compaction.
- Ideal tyres for modern farming, suitable for both on and off-the-road applications.



RIB-777



PK-303



TRENCHER



I-1 FARM SERVICE



PK-305



PK-307

SIZE	PATTERN	PLY RATING	RIM WIDTH	TT or TL	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD	LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED		
					mm	inch	mm	inch	mm	inch	mm	inch		mm	inch	kg	lbs		bar	psi	kmph
7.00-12	PK-303	6	4.25	TL	185	7.3	665	26.2	305	12.0	1956	77.0	8	10	750	1650	3.4	48	98	A8/40 kmph	A8/25mph
300/65-12	RIB-777	8	9.0	TL	305	12.0	685	27.0	305	12.0	2007	79.0	8	10	1500	3300	3.6	51	122	A8/40 kmph	A8/25mph
10.0/80-12	PK-303	8	9.0	TL	264	10.4	710	28.0	305	12.0	2083	82.0	8	9	1250	2750	4.2	60	116	A8/40 kmph	A8/25mph
	PK-303	10	9.0	TL	264	10.4	710	28.0	305	12.0	2083	82.0	8	9	1420	3124	5.4	77	121	A8/40 kmph	A8/25mph
23x10.50-12	TRENCHER	6	8.5	TL	264	10.3	575	22.6	262	10.3	1697	66.8	15	19	775	1705	2.3	33	99	A3/15 kmph	A3/9mph
26x12.00-12	TRENCHER	8	10.5	TL	305	12.0	660	26.0	283	11.1	1856	73.0	17	21	1285	2827	3.0	43	117	A3/15 kmph	A3/9mph
	TRENCHER	12	10.5	TL	305	12.0	660	26.0	283	11.1	1856	73.0	17	21	1600	3520	4.5	64	124	A3/15 kmph	A3/9mph
9.5L-14	I-1 FARM SRVICE	8	7.0	TL	240	9.4	735	28.9	330	13.0	2159	85.0	6	7	1090	2398	3.0	43	111	D/65 kmph	D/40mph
11L-14	I-1 FARM SRVICE	8	8.0	TL	274	10.8	746	29.4	333	13.1	2209	87.0	7	7	1125	2475	2.4	36	112	D/65 kmph	D/40mph
200/60-14.5	RIB-777	10	6.8	TL	210	8.3	610	24.0	279	11.0	1778	70.0	9	11	1030	2266	6.9	98	109	A8/40 kmph	A8/25mph
	RIB-777	14	6.8	TL	210	8.3	610	24.0	279	11.0	1778	70.0	9	11	1150	2530	7.1	99	113	A8/40 kmph	A8/25mph
250/65-14.5	RIB-777	12	6.8	TL	260	10.2	694	27.3	279	11.0	1778	70.0	9	11	1550	1148	6.5	92	123	A8/40 kmph	A8/25mph
5.90-15	I-1 FARM SRVICE	4	4.5	TL	152	6.0	657	25.9	295	11.6	1955	77.0	5	6	522	1150	2.5	36	86	D/65 kmph	D/40mph
6.70-15	I-1 FARM SRVICE	6	4.5	TL	167	6.6	703	27.7	330	13.0	2082	82.0	5	6	730	1606	3.0	43	97	D/65 kmph	D/40mph



SIZE	PATTERN	PLY RATING	RIM WIDTH inch	TT or TL	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs		bar	psi
7.60-15	I-1 FARM SERVICE	8	5.5	TL	190	7.5	718	28.3	325	12.8	2184	86.0	5	6	800	1760	2.8	51	100	D/65 kmph	D/40mph
9.5L-15	I-1 FARM SERVICE	8	7.0	TL	241	9.5	765	30.1	330	13.0	2235	88.0	6	8	1090	2398	3.0	43	111	D/65 kmph	D/40mph
11L-15	I-1 FARM SERVICE	8	8.0	TL	270	10.6	790	31.1	330	13.0	2261	89.0	8	10	1150	2530	2.5	36	113	D/65 kmph	D/40mph
	I-1 FARM SERVICE	12	8.0	TL	270	10.6	790	31.1	330	13.0	2261	89.0	8	10	1450	3190	3.6	51	121	D/65 kmph	D/40mph
	I-1 FARM SERVICE	20	8.0	TL	270	10.6	790	31.1	330	13.0	2261	89.0	8	10	1964	4320	5.3	75	131	D/65 kmph	D/40mph
12.5L-15	I-1 FARM SERVICE	8	10.0	TL	310	12.2	818	32.2	356	14.0	2413	95.0	9	11	1360	2992	2.5	36	119	D/65 kmph	D/40mph
	I-1 FARM SERVICE	12	10.0	TL	310	12.2	818	32.2	356	14.0	2413	95.0	9	11	1750	3850	3.7	52	128	D/65 kmph	D/40mph
	I-1 FARM SERVICE	16	10.0	TL	310	12.2	818	32.2	356	14.0	2413	95.0	9	11	2023	4450	4.6	65	132	D/65 kmph	D/40mph
	I-1 FARM SERVICE	24	10.0	TL	310	12.2	818	32.2	356	14.0	2413	95.0	9	11	2727	6000	5.5	78	143	D/65 kmph	D/40mph
31X13.50-15	I-1 FARM SERVICE	8	10.0	TL	347	13.7	779	30.7	351	13.8	2134	84.0	9	11	1181	2600	3.2	45	114	D/65 kmph	D/40mph
	I-1 FARM SERVICE	12	10.0	TL	347	13.7	779	30.7	351	13.8	2134	84.0	9	11	1600	3520	5.3	75	124	D/65 kmph	D/40mph
29X12.50-15	TRENCHER	8	10.0	TL	310	12.2	745	29.3	320	12.6	1950	76.8	20	25	850	1870	2.4	34	102	A3/15kmph	A3/9mph
31X15.50-15	TRENCHER	10	13.0	TL	394	15.5	795	31.3	358	14.0	2362	93.0	23	29	1450	3190	3.5	50	121	A3/15kmph	A3/9mph
10.0/75-15.3	PK-303	10	9.0	TL	264	10.4	760	29.9	356	14.0	2235	88.0	8	10	1550	3410	5.2	74	123	A8/40kmph	A8/25mph
	PK-303	12	9.0	TL	264	10.4	760	29.9	356	14.0	2235	88.0	8	10	1700	3750	6.4	91	126	A8/40kmph	A8/25mph
	PK-303	14	9.0	TL	264	10.4	760	29.9	356	14.0	2235	88.0	8	10	1900	4180	7.1	101	130	A8/40kmph	A8/25mph
	PK-303	18	9.0	TL	264	10.4	760	29.9	356	14.0	2235	88.0	8	10	2360	5192	7.1	101	138	A8/40kmph	A8/25mph
	PK-303	22	9.0	TL	264	10.4	760	29.9	356	14.0	2235	88.0	8	10	2750	6050	7.5	108	143	A3/15kmph	A8/25mph
11.5/80-15.3	PK-303	10	9.0	TL	290	11.4	845	33.2	381	15.0	2464	97.0	9	11	1950	4300	4.6	65	131	A8/40kmph	A8/25mph
	PK-303	12	9.0	TL	290	11.4	845	33.2	381	15.0	2464	97.0	9	11	2180	4800	5.6	79	135	A8/40kmph	A8/25mph
	PK-303	14	9.0	TL	290	11.4	845	33.2	381	15.0	2464	97.0	9	11	2430	5346	6.5	92	139	A8/40kmph	A8/25mph
	PK-303	16	9.0	TL	290	11.4	845	33.2	381	15.0	2464	97.0	9	11	2575	5675	7.1	101	141	A8/40kmph	A8/25mph
	PK-303	18	9.0	TL	290	11.4	845	33.2	381	15.0	2464	97.0	9	11	2900	6375	7.8	111	145	A8/40kmph	A8/25mph
	PK-303	22	9.0	TL	290	11.4	845	33.2	381	15.0	2464	97.0	9	11	3250	7150	7.9	112	149	A8/40kmph	A8/25mph
12.5/80-15.3	PK-303	14	9.0	TL	315	12.4	890	35.0	381	15.0	2591	102.0	9	11	2650	5825	5.9	84	142	A8/40kmph	A8/25mph
	PK-303	16	9.0	TL	315	12.4	890	35.0	381	15.0	2591	102.0	9	11	2800	6160	6.5	92	144	A8/40kmph	A8/25mph
	PK-303	18	9.0	TL	315	12.4	890	35.0	381	15.0	2591	102.0	9	11	3450	7600	6.3	89	151	A8/40kmph	A8/25mph
280/60-15.5	PK-303	14	9.0	TL	280	11.0	730	28.7	381	15.0	2565	101.0	9	11	1800	3960	4.0	57	128	A8/40kmph	A8/25mph
400/60-15.5	PK-305	10	13.0	TL	404	15.9	874	34.4	381	15.0	2565	101.0	10	11	2430	5346	2.8	40	139	A8/40kmph	A8/25mph
	PK-305	14	13.0	TL	404	15.9	874	34.4	381	15.0	2565	101.0	10	11	2725	5995	5.0	71	143	A-8/40kmph	A8/25mph
	PK-305	18	13.0	TL	404	15.9	874	34.4	381	15.0	2565	101.0	10	11	3250	7150	6.1	87	149	A8/40kmph	A8/25mph
6.00-16	I-1 FARM SERVICE	8	4.5	TL	165	6.5	720	28.3	335	13.2	2134	84.0	7	9	690	1518	3.0	43	95	D/65 kmph	D/40mph
6.50-16	I-1 FARM SERVICE	10	4.5	TL	175	6.9	750	29.5	335	13.2	2134	84.0	7	9	800	1760	3.0	43	100	D/65 kmph	D/40mph
7.00-16	I-1 FARM SERVICE	12	5.5	TL	180	7.1	715	28.1	348	13.7	2210	87.0	7	9	909	2000	3.0	43	104	D/65 kmph	D/40mph
7.50-16	I-1 FARM SERVICE	12	5.5	TL	190	7.5	745	29.3	360	14.2	2311	91.0	7	9	1218	2680	4.2	60	115	D/65 kmph	D/40mph
10.5/65-16	PK-303	10	9.0	TL	274	10.8	755	29.7	356	14.0	2210	87.0	8	10	1550	3410	5.3	75	123	A8/40kmph	A8/25mph
	PK-303	14	9.0	TL	274	10.8	755	29.7	356	14.0	2210	87.0	8	10	1900	4180	7.3	104	130	A8/40kmph	A8/25mph
280/70-16	PK-303	10	9.0	TL	280	11.0	780	30.7	363	14.3	2250	88.6	8	10	1250	2750	2.4	34	116	A8/40kmph	A8/25mph
11L-16	I-1 FARM SERVICE	8	8.0	TL	270	10.6	795	31.3	356	14.0	2337	92.0	7	9	1215	2992	2.5	36	130	D/65 kmph	D/40mph
12.5L-16	I-1 FARM SERVICE	12	10.0	TL	310	12.2	845	33.2	381	15.0	2464	97.0	8	10	1800	3960	3.7	52	130	D/65 kmph	D/40mph
13.0/55-16	PK-303	10	11.0	TL	336	13.2	770	30.3	356	14.0	2261	89.0	9	11	2060	4532	4.9	70	133	A8/40kmph	A8/25mph
	PK-303	14	11.0	TL	336	13.2	770	30.3	356	14.0	2261	89.0	9	11	2240	4928	5.8	84	136	A8/40kmph	A8/25mph
13.0/70-16	PK-303	10	11.0	TL	336	13.2	770	30.3	356	14.0	2261	89.0	9	11	2060	4532	4.8	70	133	A8/40kmph	A8/25mph
13.0/70-16	PK-303	14	11.0	TL	336	13.2	770	30.3	356	14.0	2261	89.0	9	11	2240	4928	5.7	82	136	A8/40kmph	A8/25mph
13.0/75-16	PK-303	10	11.0	TL	340	13.4	900	35.4	406	16.0	2718	107.0	9	11	2360	5192	4.1	60	138	A8/40kmph	A8/25mph
13.0/75-16	PK-303	14	11.0	TL	340	13.4	900	35.4	406	16.0	2718	107.0	9	11	2841	6250	5.7	82	144	A8/40kmph	A8/25mph
14.0/65-16	PK-303	14	11.0	TL	353	13.9	871	34.3	381	15.0	2540	100.0	9	11	2900	6380	5.6	80	145	A8/40kmph	A8/25mph
14L-16.1	I-1 FARM SERVICE	8	11.0	TL	355	14.0	927	36.5	419	16.5	2565	101.0	9	11	1800	3960	2.3	33	128	D/65kmph	D/40mph
	I-1 FARM SERVICE	12	11.0	TL	355	14.0	927	36.5	419	16.5	2565	101.0	9	11	2120	4664	3.1	44	134	D/65kmph	D/40mph
16.5L-16.1	I-1 FARM SERVICE	10	14.0	TL	434	17.1	1023	40.3	455	17.9	2794	110.0	12	15	2360	5192	2.5	36	138	B/50kmph	B/30mph
19.5L-16.1	I-1 FARM SERVICE	12	16.0	TL	490	19.3	1023	40.3	470	18.5	2921	115.0	12	15	2725	5995	2.2	31	143	B/50kmph	B/30mph
21.5L1-6.1	I-1 FARM SERVICE	10	18.0	TL	533	21.0	1102	43.4	490	19.3	3048	120.0	12	15	3000	6600	1.9	27	146	B/50kmph	B/30mph
	I-1 FARM SERVICE	14	18.0	TL	553	21.0	1102	43.4	490	19.3	3048	120.0	12	15	3550	7810	2.5	36	152	B/50kmph	B/30mph
15.0/55-17	PK-305	10	13.0	TL	391	15.4	850	33.5	381	15.0	2489	98.0	9	11	2120	4664	3.6	51	134	A8/40kmph	A8/25mph
	PK-305	14	13.0	TL	391	15.4	850	33.5	381	15.0	2489	98.0	9	11	2575	5665	4.9	70	141	A8/40kmph	A8/25mph
19.0/45-17	PK-307	14	16.0	TL	491	19.3	870	34.3	381	15.0	2540	100.0	10	13	2800	6160	3.9	55	144	A8/40kmph	A8/25mph
	PK-307	18	16.0	TL	491	19.3	870	34.3	381	15.0	2540	100.0	10	13	4000	8800	4.5	64	156	A8/40kmph	A8/25mph
500/50-17	PK-307	14	16.0	TL	503	19.8	945	37.2	381	15.0	2490	98.0	11	14	3550	7810	3.8	54	152	A8/40kmph	A8/25mph
	PK-307	18	16.0	TL	503	19.8	945	37.2	381	15.0	2490	98.0	11	14	4125	9075	4.8	68	157	A8/40kmph	A8/25mph
10.5/80-18	PK-303	10	9.0	TL	275	10.8	885	35.0	406	16.0	2591	102.0	10	13	1450	3190	5.5	78	121	A8/40km/h	A8/25mph
12.5/80-18	PK-303	12	9.0	TL	308	12.1	965	38.0	432	17.0	2819	111.0	10	13	2650	5830	5.0	71	142	A8/40km/h	A8/25mph
	PK-303	16	9.0	TL	308	12.1	965	38.0	432	17.0	2819	111.0	10	13	3350	7370	6.7	95	150	A8/40km/h	A8/25mph
13.0/65-18	PK-303	16	11.0	TL	336	13.2	890	35.0	406	16.0	2616	103									